

254-757-1177 | sales@hirail-wise.com | hirail-wise.com

## **SPECIFICATIONS**

Truck	3 axle Tier IV compliant
Aerial Platform	
Dimensions	8' x 16'
Rotation	Pivots ± 90° from center
Platform/Working Height	20'/25'
Platform Elevator	
Load Capacity on Tires	1200 lb (544 kg)
Load Capacity on Rails	2000 lb (907 kg)
Rail Gear	Under-cab and Rear (meets FRA)
	,
Rail Drive System	Creep drive system installed allows
Rail Drive System	Creep drive system installed allows for movement on rails up to 5mph by
Rail Drive System	<del>*</del> '
Rail Drive System  Wire Manipulator	for movement on rails up to 5mph by
,	for movement on rails up to 5mph by remote control
,	for movement on rails up to 5mph by remote control  2, with a 27' max height



U.S. Patent No. 10,173,875

## **FEATURES**

- Radio remote system controls Rail Drive, Wire Manipulator Arm, Platform and optional Wire Stagger/Height Measuring System
- Back up camera and alarm is active on tires/rail gear and turns to side view when using signals
- Hydraulic fold down handrails reduce the overall height of the truck and can be raised or lowered from the steps
- Steps at rear of truck are for safe and easy access to the platform
- Rail Safety lights system in both directions
- Interlock systems
- Emergency Platform Lowering System
- Hydraulic E-stop on rear and side with guard
- Engine stop/start from rear and side control panel
- Can be used on rail or off rail without outriggers















SAFELY

KEEPING YOU ON TRACK



Material and specifications are subject to change without notice. Units in photos may include optional features. Contact a RailWise representative for available options. RailWise® and the RailWise logo are registered trademarks of Fritel & Associates, LLC and may not be used without permission.

© 2024 Diversified Product Development All Rights Reserved.

